Star Estimating 118-20 229th St, Cambria Heights, NY 11411,USA

Email: info@starestimating.com Website: www.starestimating.com

DIV.01	GENERAL CONDITIONS				MEASURMENT	Labor	Material	TOTAL COST	COST
									\$ -
	Permits Documentation And Fees	1	0%	1	LS			\$ -	
	Hazardous Waste Or Disposal Work	1	0%	1	LS			\$ -	
	Signage	1	0%	1	LS			\$ -	
	Supervisory Personnel	1	0%	1	LS			\$ -	
	Lighting And Power	1	0%	_1	LS			\$ -	
	Toilet Facilities	1	0%	1	LS			\$ -	
	Material Storage	1	0%	1	LS			\$ -	
	Cleaning	1	0%	1	LS			\$ -	
DIV.03	CONCRETE								\$ 413,202.55
			200	8					
	Concrete For Slabs								
				-					
	5" Thick Concrete Slab On Grade Reinforced W/		Name .						
	6X6-W2.9 X W2.9 W.W.F. Placed 2" Clear From		1						
	Top Of Slab	153	10%	168	SF	\$ 3.21	\$ 4.30	\$ 1,263.93	
	6" Thick Concrete Slab On Grade Reinforced W/ 6X6-W2.9X W2.9 W.W.F. Placed 2-1/2" Clear From Top Of Slab Over Granular Sub Base And	4005	10%	5405	95	¢ 2.21	¢ 476	¢ /2 701 17	
	·	4990	10 /8	3493	J J	φ 3.21	φ 4.70	φ 45,791.17	
	@16" O.C. And #5 Bottom Rebars @12" O.C. And	= S ₂₀₂	10%	222		\$ 3.24	\$ 4.50	\$ 1,719.83	
	New High-Bay Concrete Slab On Grade 10" Thick Reinforced W/ #5 Rebars @18" O.C. Both Ways Placed 4" Clear From Top Of Slab Over 6"	3756	10%	4132	SF	\$ 3.24	\$ 4.50	\$ 31,978.58	
		Lighting And Power Toilet Facilities Material Storage Cleaning CONCRETE Concrete For Slabs 5" Thick Concrete Slab On Grade Reinforced W/6X6-W2.9 X W2.9 W.W.F. Placed 2" Clear From Top Of Slab 6" Thick Concrete Slab On Grade Reinforced W/6X6-W2.9X W2.9 W.W.F. Placed 2-1/2" Clear From Top Of Slab Over Granular Sub Base And Compacted Grade Over Vapor Barrier Concrete Stoop Slab Reinforced W/#5 Rebars @16" O.C. And #5 Bottom Rebars @12" O.C. And #5 Bent Bars @12" O.C. W/#5 X2'-6" Dowels Embed Into Site Paving @12" O.C. New High-Bay Concrete Slab On Grade 10" Thick Reinforced W/#5 Rebars @18" O.C. Both Ways	Lighting And Power Toilet Facilities Material Storage Cleaning 1 Concrete For Slabs 5" Thick Concrete Slab On Grade Reinforced W/ 6X6-W2.9 X W2.9 W.W.F. Placed 2" Clear From Top Of Slab 6" Thick Concrete Slab On Grade Reinforced W/ 6X6-W2.9X W2.9 W.W.F. Placed 2" Clear From Top Of Slab Or Grade Reinforced W/ 6X6-W2.9X W2.9 W.W.F. Placed 2-1/2" Clear From Top Of Slab Over Granular Sub Base And Compacted Grade Over Vapor Barrier Concrete Stoop Slab Reinforced W/ #5 Rebars @16" O.C. And #5 Bottom Rebars @12" O.C. And #5 Bent Bars @12" O.C. W/ #5 X2'-6" Dowels Embed Into Site Paving @12" O.C. New High-Bay Concrete Slab On Grade 10" Thick Reinforced W/ #5 Rebars @18" O.C. Both Ways Placed 4" Clear From Top Of Slab Over 6"	Lighting And Power Toilet Facilities Material Storage Cleaning 1 0% Cleaning 1 0% DIV.03 CONCRETE Concrete For Slabs 5" Thick Concrete Slab On Grade Reinforced W/ 6X6-W2.9 X W2.9 W.W.F. Placed 2" Clear From Top Of Slab 6" Thick Concrete Slab On Grade Reinforced W/ 6X6-W2.9X W2.9 W.W.F. Placed 2" Clear From Top Of Slab 0" Thick Concrete Slab On Grade Reinforced W/ 6X6-W2.9X W2.9 W.W.F. Placed 2-1/2" Clear From Top Of Slab Over Granular Sub Base And Compacted Grade Over Vapor Barrier 4995 Concrete Stoop Slab Reinforced W/ #5 Rebars @16" O.C. And #5 Bottom Rebars @12" O.C. And #5 Bent Bars @12" O.C. W/ #5 X2'-6" Dowels Embed Into Site Paving @12" O.C. New High-Bay Concrete Slab On Grade 10" Thick Reinforced W/ #5 Rebars @18" O.C. Both Ways Placed 4" Clear From Top Of Slab Over 6"	Lighting And Power 1 0% 1 Toilet Facilities 1 0% 1 Material Storage 1 0% 1 Cleaning 1 0% 1 DIV.03 CONCRETE Concrete For Slabs 5" Thick Concrete Slab On Grade Reinforced W/ 6X6-W2.9 X W2.9 W.W.F. Placed 2" Clear From Top Of Slab 153 10% 168 6" Thick Concrete Slab On Grade Reinforced W/ 6X6-W2.9X W2.9 W.W.F. Placed 2-1/2" Clear From Top Of Slab Over Granular Sub Base And Compacted Grade Over Vapor Barrier 4995 10% 5495 Concrete Stoop Slab Reinforced W/ #5 Rebars @16" O.C. And #5 Bent Bars @12" O.C. W/ #5 X2'-6" Dowels Embed Into Site Paving @12" O.C. 202 10% 222 New High-Bay Concrete Slab On Grade 10" Thick Reinforced W/ #5 Rebars @18" O.C. Both Ways Placed 4" Clear From Top Of Slab Over 6"	Lighting And Power	Lighting And Power	Lighting And Power	Lighting And Power 1 0% 1 LS \$ - Toilet Facilities 1 0% 1 LS \$ - Material Storage 1 0% 1 LS \$ - Material Storage 1 0% 1 LS \$ - Cleaning 1 0% 1 LS \$ - Cleaning 1 0% 1 LS \$ - Cleaning 1 0 0% 1 0 0% 1 LS \$ - Cleaning 1 0 0% 1 0 0% 1 0 0% 1 0 0% 1 0 0% 1 0 0% 1 0 0% 1 0 0 0 0

	Concrete For Footing/Foundations								
13	Concrete For Footing Reinforced W/ (2) #5 Continuous Rebars	4.074074074	10%	4	CY	\$ 355.00	\$ 450.00) \$	3,607.59
14	Concrete For Footing Reinforced W/ (3) #5 Continuous Rebars	3.481481481	10%	4	CY	\$ 355.00	\$ 450.00		3,082.85
15	Concrete For Footing Reinforced W/ (4) #5 Doweled Bent Top Bars Each Side Epoxide Into Existing Foundation Wall 7" Using Hilti Hit-Hy 200 Adhesive And (4) #5 Bars Each Side And (2) #5 Rebars Side Bars Each Side W/ (4) #5 Doweled Bent Bottom Bars Each Side Epoxied Into Existing Footing 7" Using Hilti Hit-Hy 200 Adhesive And (3) #5 Bottom Bars Each Side	9.481481481	10%	10	CY	\$ 355.00	\$ 450.00) \$	8,395.85
16	Concrete For Foundation Reinforced W/ #5 Horizontal Rebars @18" O.C. And #5 Vertical @12" O.C. W/ #5 Bent Bars @12" O.C.	5.851851852	10%	6	CY	\$ 355.00	\$ 450.00	\$	5,181.81
17	Concrete For Foundation Wall Reinforced W/ #5 Rebars Horizontal @14" O.C. And #5 Rebars Vertical @12" O.C. W/ #5 Bent Bars @12" O.C.	6.148148148	10%	7	CY	\$ 355.00	\$ 450.00		
	Reinforcement	V	=					#	
18	(2) #5 X3'-0" Rebars	7	0%	7	EA	\$ 3.45	\$ 7.60) \$	77.35
19	3/4" Dia X16" Long Smooth Dowels @12" O.C. Grease End In Paving To Prevent Bond	386	0%	386	EA	\$ 2.32	\$ 5.40	\$	2,979.92
20	3/4" Dia X16" Long Smooth Dowels @24" O.C. Grease End In Paving To Prevent Bond	132	0%	132	EA	\$ 1.76	\$ 5.40	\$	945.12
	Slab Void Forms				/			\pm	
21	Cardboard Carton Void Form	72	10%	79	SF	\$ 2.30	\$ 5.40	\$	609.84
	Joint Sealant							#	
22	1/2" Expansion Joint Sealant	1092	10%	1201	LF	\$ 0.78	\$ 1.23		2,414.41
23	Zip Strip And Sealant	343	10%	377	LF	\$ 0.56		_	648.96
24	Bond Breaking Tape	549	10%	604	LF	\$ 0.71	\$ 1.10) \$	1,093.06

										Π	
	Concrete For Spread Footings										
25	F1.5: Concrete For Footing Reinforced W/ (2) #4 Rebars Eachway	0.185185185	10%	0	CY	\$	355.00	\$ 4	450.00	\$	163.98
26	F3.0: Concrete For Footing Reinforced W/ (5) #4 Rebars Eachway	1.45	10%	2	CY	\$	355.00	\$ 4	450.00	\$	1,283.98
27	Concrete For Ground Mounted Street Name Sign Footing	0.87	10%	1	CY	\$	355.00	\$ 4	450.00	\$	770.39
	Gravels										
28	4" Thick Crushed Limestone Base(Size: 3/4" Crushed)	5655	10%	6221	CF	\$	1.21	\$	7.60	\$	54,802.61
29	4" Gravel Base Over Front Porch Stoop	3242	10%	3566	CF	\$	1.21	\$	7.60	\$	31,418.22
30	4" Gravel Base Over Garage Slab	166	10%	183	CF	\$	1.21	\$	7.60	\$	1,608.71
31	2" Washed Stones For Base Layer Of Perimeter Drain	1998	10%	2198	CF	\$	1.21	\$	7.60	\$	19,362.62
32	6" Washed Stone Cover For Perimeter Drain	12343	10%	13577	CF	\$	1.21	\$	7.60	_	119,616.01
			1 1 2	1-11							
	Concrete Grouting		100								
33	Concrete Grouting @Beam Pockets	2	0%	2	EA	\$	23.40	\$	34.60	\$	116.00
	Slab Vapor Barrier		-								
34	6 Mil. Poly Vapor Barrier	1279	10%	1407	SF	\$	0.78	\$	1.10	\$	2,646.38
35	6 Mil. Poly Vapor Barrier	531	10%	584	SF	\$	0.78	\$	1.10	\$	1,098.69
	Stairs				1						
36	Precast Concrete Steps, (3'-0" Long X 0'-11" Wide)	60	0%	60	TREADS	\$	154.30	\$ ^	189.00	\$	20,598.00
	Wide)	500	076	161		Ψ	101.00	Ψ	100.00	۳	20,000.00
	Concrete Sidewalks	500			والالالا						
37	Separated Reverse Slope 4" Thick Concrete Sidewalk (3000 Psi) (3-1/2" Slump), Reinforced W/ #3 Rebars @18" O.C. W/ Medium Broom Finish	2959	10%	3255	SF	\$	3.21	\$	4.60	\$	25,420.77

		Curbs/Gutters												
38		Concrete Curb And Gutter	520.3	10%	572	LF	\$	14.50	\$	22.30	\$ 2	21,061.74		
	DIV.31	EARTHWORK	-										\$	5,023.34
	DIV.01	LAKIIWOKK											_	- 0,020.0 .
39		Existing Critical Slopes To Be Impacted Excavate Land With Favorable Site Conditions. Stake Excavation Location. Verify Dig Safe. Remove Soil And Rocks To Specified Depth. Includes Planning, Equipment And Material Acquisition, Area Preparation And Protection, Setup And Cleanup. Filling Soil By Mechanical Means	124.4 322	10% 10%	137 354	CY CY	\$	7.80 7.80		2.43 2.43		1,399.87 3,623.47		
-10		NOTES		1070	001	01		TOTAL	Ψ	2.10	ΙΨ	0,020.11	\$	418,225.89
		This sheet is your property and you can use a	nd change the	information	as per need	d.	OVE	RHEAD				9%	\$	37,640.33
		We always convince our clients to pu	t their own pric	es for the it	ems.		CON	TRACTO	DR'S	PROF		8%	\$	33,458.07
		All data in the estimate is taken with the help of	-					JRANCE				5%	\$	20,911.29
	In (case of anything missing, we might put allowand				r need.		TINGEN	CY (CHAR		3%	\$	12,546.78
		We look forward to work with you in the f	uture as every	client is our	r priority.		TOT	AL BID					\$	522,782.36
		Starl	Est	im	af	ding	9							